



Retail  
Hospitality  
Healthcare  
Architectural Lighting  
Signage  
Casino Design  
Residential

eoslight.com



## LUMINAIRE PHOTOMETRIC TEST REPORT

### 6000k-48 x 24-HP-4SL\_IESNA95

NAME: LF-24V-48*24-6000-ASL-HP	TYPE: EOS Cloud Luminaire	WEIGHT: 4000G
SPEC.:	DIM.:	SERIAL No.: EOS
MFR.: EOS	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 30.69 lm/W
MODEL		Imax(cd)	360.0	S/MH(C0/180)	1.52	
NOMINAL POWER(W)	43.7	LOR(%)	106.7	S/MH(C90/270)	1.37	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1344.6	$\eta$ UP,DN(C0-180)	0.0,51.5	
NOMINAL FLUX(lm)	1259.93	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,55.2	
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.50	
TEST VOLTAGE(V)	24.4	$\eta$ down(%)	106.7	CIBSE SHR MAX	1.55	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2019-06-03

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.293  
Humidity: 65.0%  
Test Distance: 9.180m [K=1.0000]  
Remarks: DWY




Retail  
Hospitality  
Healthcare  
Architectural Lighting  
Signage  
Casino Design  
Residential

eoslight.com

### AAI Figure

NAME: LF-24V-48*24-6000-ASL-HP	TYPE: EOS Cloud Luminaire	WEIGHT: 4000G
SPEC.:	DIM.:	SERIAL No.: EOS
MFR.: EOS	SUR.:	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2019-06-03

γ Range: 0 - 90DEG  
γ Interval: 0.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.293  
Humidity: 65.0%  
Test Distance: 9.180m [K=1.0000]  
Remarks: DWY







