



Retail  
Hospitality  
Healthcare  
Architectural Lighting  
Signage  
Casino Design  
Residential

eoslight.com


## LUMINAIRE PHOTOMETRIC TEST REPORT

### 6000k-48 x 24-SP-4SL\_IESNA95


NAME: LF-24V-48*24-6000-ASL-SP	TYPE: EOS Cloud Luminaire	WEIGHT: 4000G
SPEC.:	DIM.:	SERIAL No.: EOS
MFR.: EOS	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 31.88 lm/W
MODEL		Imax(cd)	340.3	S/MH(C0/180)	1.50	
NOMINAL POWER(W)	39.3	LOR(%)	100.2	S/MH(C90/270)	1.35	
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1259.9	$\eta$ UP,DN(C0-180)	0.0,49.6	
NOMINAL FLUX(lm)	1257.74	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,50.6	
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.50	
TEST VOLTAGE(V)	24.4	$\eta$ down(%)	100.2	CIBSE SHR MAX	1.55	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT: lx)



C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2019-06-03

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.293  
Humidity: 65.0%  
Test Distance: 9.180m [K=1.0000]  
Remarks: DWY




Retail  
Hospitality  
Healthcare  
Architectural Lighting  
Signage  
Casino Design  
Residential

eoslight.com

### AAI Figure

NAME: LF-24V-48*24-6000-ASL-SP	TYPE: EOS Cloud Luminaire	WEIGHT: 4000G
SPEC.:	DIM.:	SERIAL No.: EOS
MFR.: EOS	SUR.:	Shielding Angle:



**Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.**

C Range: 0 - 360DEG  
C Interval: 5.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: DAMIN  
Test Date: 2019-06-03

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 0.5DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.293  
Humidity: 65.0%  
Test Distance: 9.180m [K=1.0000]  
Remarks: DWY



**γ Range:** 0 - 90DEG  
**γ Interval:** 0.5DEG  
**Test System:** EVERFINE GO-2000A\_V1 SYSTEM V2.0.293  
**Humidity:** 65.0%  
**Test Distance:** 9.180m [K=1.0000]  
**Remarks:** DWY







**γ Range:** 0 - 90DEG  
**γ Interval:** 0.5DEG  
**Test System:** EVERFINE GO-2000A\_V1 SYSTEM V2.0.293  
**Humidity:** 65.0%  
**Test Distance:** 9.180m [K=1.0000]  
**Remarks:** DWY